



Name: _____

Date: _____

Event/Location/Track: _____

Weather: _____

TRACK CONDITIONS (check all that apply)

- | | | | | |
|---------------------------------|--------------------------------------|-----------------------------------|--------------------------------------|---------------------------------------|
| <input type="checkbox"/> Indoor | <input type="checkbox"/> Outdoor | <input type="checkbox"/> Wet | <input type="checkbox"/> Dry | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Tight | <input type="checkbox"/> Open | <input type="checkbox"/> Low Bite | <input type="checkbox"/> Medium Bite | <input type="checkbox"/> High Bite |
| <input type="checkbox"/> Smooth | <input type="checkbox"/> Loose/Loomy | <input type="checkbox"/> Rough | <input type="checkbox"/> Blue Groove | <input type="checkbox"/> Other: _____ |

DIFFERENTIAL

- Stock: AX30392 38/13
- MACHINED OPTIONS**
- Option: AX30395 38/13
- Option: AX30401 36/14
- Option: AX30402 43/13

DIFFERENTIAL OIL

Front Center Rear

FRONT SHOCKS

Pre-Load: _____ mm

Pistons:

DELTRIN

TOP D, E

E, D

Length: _____ mm

Springs: _____

Oil: _____

REAR SHOCKS

Pre-Load: _____ mm

Pistons:

DELTRIN

TOP D, E

E, D

Length: _____ mm

Springs: _____

Oil: _____

FRONT LINKS

UPPER

Length: _____ mm

STEERING LINK

Length: _____ mm

REAR LINKS

UPPER

Length: _____ mm

GEARING (32P)

Pinion: _____

Spur: 48 50

52 54

Plastic Steel

FRONT SUSPENSION

AX30825 Only

Toe Block

F1

F2

AX30803 Exo Sway Bar Only

_____ 1.5mm

_____ 1.7mm

_____ 1.9mm

Ride Height: _____ mm

STEERING & WHEELBASE

Steering Rack

AX30815 Only _____

Wheelbase

Spacers

REAR SUSPENSION

AX30826 Only

Toe Block

R1

R2

AX30804 Exo Sway Bar Only

_____ Soft

_____ Medium

_____ Hard

Ride Height: _____ mm

TIRES/FOAMS

Front Tire: _____

Front Foam: _____

Front Rim: _____

Rear Tire: _____

Rear Foam: _____

Rear Rim: _____

ELECTRONICS

Transmitter: _____

Steering Servo: _____

Motor: _____

Battery: _____

ESC: _____

NOTES