

:: Driver: Team Associated **:: Date:** _____
:: Track: Standard RC8T Setup
:: Event: _____

Setup Sheet for Team Associated's RC8T

Rev. 1

:: Front Suspension

anti-roll bar:
☐ 2.2 - black
☒ 2.5 - silver
☐ 2.8 - gold

steering rack:
☐ back
☐ mid
☐ front

hinge pin bushing
 # 2
☐ up ☒ down

camber: -2 °

caster: 16 °

toe: 0 °

ride height: 37mm

kickup bushing
 # 2
☒ up ☐ down

:: Rear Suspension

anti-roll bar:
☐ 2.2 - black
☐ 2.5 - silver
☒ 2.8 - gold

wheelbase:
☐ long
☒ medium
☐ short

camber: -2 °

toe: 3 °

hub:
☐ upper
☐ lower

ride height: 43mm

anti-squat bushing
 # 2
☐ up ☒ down

:: Front Shocks

spring: (5.1 lb) silver piston: 1.6
 shock fluid: 50 wt. length: 113mm
 shock cap: _____

:: Rear Shocks

spring: (3.3 lb) silver piston: 1.6
 shock fluid: 50 wt. length: 125mm
 shock cap: _____

:: Differentials

front fluid: 7000cst
 center fluid: 7000cst
 rear fluid: 7000cst

:: Wing

location: ☐ forward ☒ back
 angle: ☒ low ☐ med. ☐ high
 type: _____

:: Chassis Braces

☒ standard ☐ molded ☐ aluminum
 other: _____

:: Engine

engine: 30% recommended restrictor: _____
 muffler: _____ temp: _____
 glow plug: _____
 fuel: _____

:: Gearing/Clutch

gearing: 14/54
 shoes: 3 x aluminum _____ x fiber
 spring: _____ x .9mm 3 x 1.0mm _____ x 1.1mm
 notes: _____

:: Notes

:: Tires

tire (F/R): _____ / _____
 compound (F/R): _____ / _____
 insert: _____ wheel: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq: ☐
 comments: _____

:: Track Info

traction: ☐ high ☐ med. ☐ low
 surface: ☐ smooth ☐ bumpy
☐ blue groove ☐ soft dirt ☐ grass
☐ clay ☐ wet ☐ dusty
 other: _____