




SB-2264MG




Line	MONSTER LINE
Application	CAR AIRPLANE
Servo Size	Low Profile
Operating Voltage	6.0V-8.4V
Speed	0.08 s/60°
Torque	19 kg/cm 263.9 oz/in
Amplifier Type	Digital Controller
Motor Type	Original Brushless
Case Type	Aluminum
Protection	Water Resistant
Dimensions (L x W x H)	40.8 x 20.2 x 25.75 mm
Weight	57 g
Gear Type	Heavy-Duty Metal

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Normal	Potentiometer	VR
Speed @6.0V	0.11 s/60°	Cable	22 AWG 200 ±5 mm
Torque @6.0V	12 kg/cm 166.6 oz/in	Connector	JR Connector
Speed @7.4V	0.09 s/60°	Stall Current @6.0V	3000 mA
Torque @7.4V	15 kg/cm 208.3 oz/in	Operating Current @6.0V	200 mA
Speed @8.4V	0.08 s/60°	Stall Current @7.4V	3700 mA
Torque @8.4V	19 kg/cm 263.9 oz/in	Operating Current @7.4V	220 mA
PCB Board	12-bit	Stall Current @8.4V	5000 mA
Rotating Direction	Counterclockwise (when 1000+2000 µsec)	Operating Current @8.4V	250 mA
Max Travel	~130° (when 900+2100 µsec)	Idle Current	5 mA
Operating Travel	90° (when 1000+2000 µsec)	Dead Band Width	3-5 µsec
Neutral Position	1500 µsec	Frequency Range	50-360 Hz
Horn Gear Spline	25T(Φ6)	Control System	Pulse width modification
Bearing	2x Ball Bearings	Operating Temperature	-10°C to 50°C