




SC-1201MG+




Line	HOBBY LINE
Application	CAR
Servo Size	Standard
Operating Voltage	4.8V-6.0V
Speed	0.16 s/60°
Torque	25 kg/cm 347.2 oz/in
Amplifier Type	Digital Controller
Motor Type	Coreless
Case Type	Composite
Protection	Dust Resistant
Dimensions (L x W x H)	40.75 x 20 x 42 mm
Weight	69 g
Gear Type	Heavy-Duty Metal

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	Potentiometer	VR
Speed @4.8V	0.19 s/60°	Cable	22 AWG 300 ±5 mm
Torque @4.8V	20 kg/cm 277.7 oz/in	Connector	JR Connector
Speed @6.0V	0.16 s/60°	Stall Current @4.8V	8000 mA
Torque @6.0V	25 kg/cm 347.2 oz/in	Operating Current @4.8V	300 mA
PCB Board	12-bit	Stall Current @6.0V	10000 mA
Rotating Direction	Counterclockwise (when 1500+2000 µsec)	Operating Current @6.0V	350 mA
Max Travel	~164° (when 800+2200 µsec)	Idle Current	5 mA
Operating Travel	120° (when 1000+2000 µsec)	Dead Band Width	3-5 µsec
Neutral Position	1500 µsec	Frequency Range	50-360 Hz
Horn Gear Spline	25T(Φ6)	Control System	Pulse width modification
Bearing	2x Ball Bearings	Operating Temperature	-10°C to 50°C