




SH-1357+




Line	ORIGINAL LINE
Application	CAR HELI AIRPLANE
Servo Size	Mini
Operating Voltage	4.8V-6.0V
Speed	0.07 s/60°
Torque	2.5 kg/cm 34.7 oz/in
Amplifier Type	Digital Controller
Motor Type	Coreless
Case Type	Hybrid (Aluminium/Composite)
Protection	Dust Resistant
Dimensions (L x W x H)	35 x 15 x 29.8 mm
Weight	26 g
Gear Type	High-Strength Composite

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	Potentiometer	VR
Speed @4.8V	0.09 s/60°	Cable	26 AWG 250 ±5 mm
Torque @4.8V	1.9 kg/cm 26.4 oz/in	Connector	JR Connector
Speed @6.0V	0.07 s/60°	Stall Current @4.8V	1200 mA
Torque @6.0V	2.5 kg/cm 34.7 oz/in	Operating Current @4.8V	80 mA
PCB Board	12-bit	Stall Current @6.0V	1500 mA
Rotating Direction	Counterclockwise (when 1000+2000 µsec)	Operating Current @6.0V	100 mA
Max Travel	~154° (when 800+2200 µsec)	Idle Current	5 mA
Operating Travel	110° (when 1000+2000 µsec)	Dead Band Width	3-5 µsec
Neutral Position	1500 µsec	Frequency Range	50-360 Hz
Horn Gear Spline	25T(Φ6)	Control System	Pulse width modification
Bearing	2x Ball Bearings	Operating Temperature	-10°C to 50°C