




SV-1255MG




Line	ORIGINAL LINE
Application	CAR AIRPLANE
Servo Size	Standard
Operating Voltage	6.0V-8.4V
Speed	0.075 s/60°
Torque	25 kg/cm 347.2 oz/in
Amplifier Type	Digital Controller
Motor Type	Coreless
Case Type	Hybrid (Aluminium/Composite)
Protection	Water Resistant
Dimensions (L x W x H)	40.8 x 20.2 x 26.35 mm
Weight	51 g
Gear Type	Heavy-Duty Metal

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	Potentiometer	VR
Speed @6.0V	0.1 s/60°	Cable	22 AWG 300 ±5 mm
Torque @6.0V	15 kg/cm 208.3 oz/in	Connector	JR Connector
Speed @7.4V	0.085 s/60°	Stall Current @6.0V	4000 mA
Torque @7.4V	20 kg/cm 277.7 oz/in	Operating Current @6.0V	150 mA
Speed @8.4V	0.075 s/60°	Stall Current @7.4V	5000 mA
Torque @8.4V	25 kg/cm 347.2 oz/in	Operating Current @7.4V	180 mA
PCB Board	12-bit	Stall Current @8.4V	6000 mA
Rotating Direction	Counterclockwise (when 1000+2000 µsec)	Operating Current @8.4V	220 mA
Max Travel	~160° (when 700+2300 µsec)	Idle Current	5 mA
Operating Travel	90° (when 1000+2000 µsec)	Dead Band Width	3-5 µsec
Neutral Position	1500 µsec	Frequency Range	50-360 Hz
Horn Gear Spline	25T(Φ6)	Control System	Pulse width modification
Bearing	2x Ball Bearings	Operating Temperature	-10°C to 50°C