




SV-1273TG+




Line	ORIGINAL LINE
Application	CAR AIRPLANE
Servo Size	Standard
Operating Voltage	6.0V-8.4V
Speed	0.07 s/60°
Torque	25 kg/cm 347.2 oz/in
Amplifier Type	Digital Controller
Motor Type	Coreless
Case Type	Hybrid (Aluminium/Composite)
Protection	Water Resistant
Dimensions (L x W x H)	40.3 x 20.2 x 37.2 mm
Weight	64 g
Gear Type	Titanium

DIMENSIONS



PERFORMANCE RADAR



DETAILED SPECIFICATION

Compability	Sanwa SSR	Potentiometer	VR
Speed @6.0V	0.08 s/60°	Cable	22 AWG 300 ±5 mm
Torque @6.0V	14 kg/cm 194.4 oz/in	Connector	JR Connector
Speed @7.4V	0.065 s/60°	Stall Current @6.0V	5400 mA
Torque @7.4V	20 kg/cm 277.7 oz/in	Operating Current @6.0V	130 mA
Speed @8.4V	0.07 s/60°	Stall Current @7.4V	6800 mA
Torque @8.4V	25 kg/cm 347.2 oz/in	Operating Current @7.4V	150 mA
PCB Board	12-bit	Stall Current @8.4V	8000 mA
Rotating Direction	Counterclockwise (when 1000+2000 µsec)	Operating Current @8.4V	180 mA
Max Travel	~130° (when 800+2200 µsec)	Idle Current	5 mA
Operating Travel	100° (when 1000+2000 µsec)	Dead Band Width	3-5 µsec
Neutral Position	1500 µsec	Frequency Range	50-360 Hz
Horn Gear Spline	25T(Φ6)	Control System	Pulse width modification
Bearing	2x Ball Bearings	Operating Temperature	-10°C to 50°C